

ONE-LIGHT FLUSH MOUNT

Project:

Fixture Type: Location:

Contact:

Images:

Ceiling mounted • Damp location listed PROGRESS LED



Description:

A tapered, square, linen finish glass diffuser is paired with an energy-efficient, high-performance LED source in this contemporary ceiling fixture.

Specifications:

- Brushed Nickel (-009) (plated)
- Steel Construction
- Etched White Linen glass diffuser
- LED Module is replaceable (part # 93074252)
- · Features a tapered square, linen finish glass diffuser
- Diffuser is paired with an energy-efficient, high-performance LED source.
- 2015 lumens 80.6 lumens/watt (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Fixture covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

| Input Power25wInput Voltage120 VInput Frequency60 HzLumens/LPW (Source)1770/70 (LM-82)Lumens/LPW (Delivered)1442/58.1 (LM-79)CCT3000 KCRI90+Life (hours)50,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp30° CWarranty5 year warrantyLabelsCSAus Damp location listed ENERGY STAR® qualified | | | |
|---|------------------------|-------------------------------------|---------------------|
| Input Voltage120 VDia ToInput Frequency60 HzHeiLumens/LPW (Source)1770/70 (LM-82)GlaLumens/LPW (Delivered)1442/58.1 (LM-79)GlaCCT3000 KGlaCRI90+HeiLife (hours)50,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30° CWarranty5 year warrantyLabelscCSAus Damp location listed ENERGY STAR® qualified | Number of Modules | 1 | Din |
| Input voitage120 vInput Frequency60 HzLumens/LPW (Source)1770/70 (LM-82)Lumens/LPW (Delivered)1442/58.1 (LM-79)CCT3000 KCRI90+Life (hours)50,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30° CWarranty5 year warrantyLabelscCSAus Damp location listed ENERGY STAR® qualified | Input Power | 25w | |
| Input Frequency60 HzLumens/LPW (Source)1770/70 (LM-82)Lumens/LPW (Delivered)1442/58.1 (LM-79)CCT3000 KCRI90+Life (hours)50,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30° CWarrantyS year warrantyLabelsCSAus Damp location listed ENERGY STAR® qualified | Input Voltage | 120 V | Diar Heiş |
| Lumens/LPW (Delivered) 1442/58.1 (LM-79) Gla Wich CCT 3000 K 90+ Life (hours) 50,000 (L70/TM-21) 50,000 (L70/TM-21) FCC Meets FCC Title 47, Part 15 Class B 30° C Max. Operating Temp 30° C Warranty 5 year warranty Labels CCSAus Damp location listed ENERGY STAR® qualified | Input Frequency | 60 Hz | |
| CCT3000 KWichCRI90+Life (hours)50,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30° CWarranty5 year warrantyLabelscCSAus Damp location listed ENERGY STAR® qualified | Lumens/LPW (Source) | 1770/70 (LM-82) | |
| CCT 3000 K CRI 90+ Life (hours) 50,000 (L70/TM-21) FCC Meets FCC Title 47, Part 15 Class B Min. Start Temp -30 °C Max. Operating Temp 30° C Warranty 5 year warranty Labels cCSAus Damp location listed ENERGY STAR® qualified | Lumens/LPW (Delivered) | 1442/58.1 (LM-79) | Glas Wid Heiş |
| CRI90+Life (hours)50,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30° CWarranty5 year warrantyLabelscCSAus Damp location listed ENERGY STAR® qualified | ССТ | 3000 K | |
| FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30° CWarranty5 year warrantyLabelscCSAus Damp location listed ENERGY STAR® qualified | CRI | 90+ | |
| Min. Start Temp-30 °CMax. Operating Temp30° CWarranty5 year warrantyLabelscCSAus Damp location listed ENERGY STAR® qualified | Life (hours) | 50,000 (L70/TM-21) | |
| Max. Operating Temp 30° C Warranty 5 year warranty Labels cCSAus Damp location listed ENERGY STAR® qualified | FCC | Meets FCC Title 47, Part 15 Class B | |
| Warranty 5 year warranty Labels cCSAus Damp location listed ENERGY STAR® qualified | Min. Start Temp | -30 °C | |
| Labels cCSAus Damp location listed ENERGY STAR® qualified | Max. Operating Temp | 30° C | |
| ENERGY STAR [®] qualified | Warranty | 5 year warranty | |
| | Labels | cCSAus Damp location listed | |
| Meets California Title 24 IA8-2016 | | ENERGY STAR [®] qualified | |
| ···· / / · · · | | Meets California Title 24 JA8-2016 | |



P350024-009-30

Dimensions:

Diameter: 11-1/2" Height: 4-7/8"

Glass Width: 11-1/2" Height: 4-1/2"



ONE-LIGHT FLUSH MOUNT

Ceiling mounted • Damp location listed PROGRESS LED



Dimming Notes:

P350024 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

| Lutron Diva DVELV-300P | |
|----------------------------------|--|
| Lutron Nova T NTELV-300 | |
| Lutron Caseta | |
| Lutron Ariadni AY-600P | |
| Lutron Lumea LG-603PG | |
| Leviton SureSlide 6672 | |
| Leviton SureSlide 6674 | |
| Lutron Ariadni AYCL-153P | |
| Lutron Skylark Contour CTCL-153P | |
| Lutron Diva DVCL-153P | |
| Cooper Devine AL DAL06P | |
| Lutron Maestro MACL-153M | |
| Lutron Ariadni AYLV-600P | |
| Lutron Maestro MA-600 | |
| Lutron NOVA T NTLV-600 | |
| lutron Maestro MAELV-600 | |
| Lutron spacer/system SPSELV-600 | |
| Lutron Nova N-600 | |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.