

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light Pendant

Hanging mounted • Damp location listed PROGRESS LED



Description:

These timeless and classic LED pendants feature designer oriented details and polished opal glass. Can be displayed singularly or in groupings of two or more in a variety of spaces, such as Modern Farmhouse, Coastal and Mid-Century Modern environments. Antique Bronze finish.

Specifications:

- Antique Bronze (-020) (painted)
- Steel Construction
- Glossy Opal Glass globe
- Oval shaped LED pendant
- · These timeless and classic LED pendants feature designer oriented details and polished opal glass
- · One light 9W medium LED lamp
- · Warm white, 3000K, color temperature, 90 CRI
- 624 lumens, 66 lumens per watt (source)
- Can be displayed singularly or in groupings of two or more in a variety of spaces, such as Modern Farmhouse, Coastal and Mid-Century Modern environments
- Replaceable light engine is California JA8 certified
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 JA8-2016

Performance:

Number of Modules	1	
Input Power	9w	
Input Voltage	120 V	
Input Frequency	60 Hz	
Lumens/LPW (Source)	624/66 (LM-82)	
Lumens/LPW (Delivered)	642/67.6 (LM-79)	
CCT	3000 K	
CRI	90 CRI	
Life (hours)	60,000 (L70/TM-21)	
FCC	Meets FCC Title 47, Part 15 Class B	
Min. Start Temp	-30 ℃	
Max. Operating Temp	30°C	
Warranty	5 year limited warranty	
Labels	cCSAus Damp location listed	
	ENERGY STAR® qualified	
	Meets California Title 24 JA8-2016	

P500066-020-30

Images:



Dimensions:

Diameter: 6-5/8" Height: 13-1/2"

Overall Ht. W/Cord: 124-1/2"

Glass Width: 6-5/8" Height: 10-1/2"



One-Light Pendant





P500066-020-30

Dimming Notes:

P500066 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Leviton SureSlide 6672

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron NOVA T NTLV-600

lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Lutron Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.